









LP-SMX Surface Mount Male Screw Fix – 15kg

LP-SMX	USE WITH:	INSTALL WITH:
	<p>LP-F8 LP-AF8A</p> 	3 x #6 countersink screws

INSTALLATION STEPS

<p>1 Drill out 350 hole in substrate</p> 	<p>2 Press LP-AF8A into drilled hole, fix with 3x #4 CSK screw</p> 	<p>3 Fit CP-08ST into LP-AF8A</p> 
<p>4 Press panel onto CP-08ST to mark clip position</p> 	<p>5 Locate LP-SMX into marked position on panel, install with 3 x #6 CSK screws</p> 	<p>6 Align panel and press firmly to engage clips</p> 

LP-SMX Surface Mount Male Screw Fix – 15kg

INDUSTRY FIT:



SPECIFICATIONS:

LOW PROFILE LP RANGE

The LP-SMX clip adds an extra heavy-duty option to the Low Profile Range. With a 15kg pull out load, the clip is designed for use with heavyweight panels, and is compatible with the LP-F8, and LP-AF8A. The surface mount clip installs easily with 3 x countersink #6 screws, removing the need for special tools for installation. Ideal for large and heavyweight panels with limited panel depth. NOTE: Should not be used with LP-DF8 installing into drywall substrate, due to strength of the clip.

LP-SMX



USE WITH:

LP-F8



LP-AF8A



MATERIAL:

Black glass filled nylon

MORE INFO:

Layout Guide TD-02, TD-08

BENEFITS

- Invisible panel fixing
- Installs with 3 x #6 countersink screws
- No special tools required
- 15kg pull out load per clip
- Durable design for frequent handling
- Enables non-sequential panel installation
- CNC machine compatibility
- 4mm clearance between panel and substrate
- Screw fix enables installation into wide variety of panel types

APPLICATIONS

- Heavyweight wall panels with minimal depth
- Interior panels
- Ceiling panels
- Moulded into hull
- Marine and architectural applications
- Steel, aluminium or fiberglass panels

INSTALLATION: Partially exploded through section showing typical installation method

